

CERTIFICATE

(Certificate of conformity with technical requirements in:)
API STANDARD 6FA FOURTH EDITION, JUNE 2018

Certificate No.:267103

Ref. Test report No.:267104

Name and postal address of manufacturer: DBV Valve Co., Ltd.

Tangtou Village, Oubei Street, Yongjia County,

PC: 325102, Wenzhou City, Zhejiang Province, P. R. China

(No.96 Fanhua East)

We hereby certify that the fire test on below valves have been conducted at the laboratory designated by manufacturer and witnessed by TÜV inspector according to requirements of API STANDARD 6FA FOURTH EDITION, JUNE 2018, the testing results of valves meet the requirements of API STAND ARD 6FA FOURTH EDITION, JUNE 2018

1. Description of Test Valve :

Q47F-CL1500 NPS2 Ball Valve
Ball Valve
2"
Class 1500
ASTM A105

2. Qualified Range of Valves:

Type	Ball Valves
Description of Valves	Ball Valves
Qualified Sizes (NPS) (according to API 6FA Table 4)	2",2 1/2",3",4"
Qualified Pressure Ratings (Class) (according to API 6FA Table 6)	1500;2500
Qualified Marking (according to API 6FA Para.4.5)	Qualified valves shall be permanently marked 6FA

This certificate is issued according to API STANDARD 6FA FOURTH EDITION, JUNE 2018, based upon the result of testing report on above mentioned test valve. The additional valves qualification shall be limited on similar valves of same basic design as the test valve and same nonmetallic materi als as the test valve in the seat-to-closure member seal, seat-to-body seal, stem seal, and body joint and seal according to API STANDARD 6FA FOURTH EDITION, JUNE 2018, Para.5.

Shanghai, January 10, 2020 (Place, date)

TÜV SÜD Industrie Service GmbH

Westendstr.199 80686 München Germany



CERTIFICATE

(Certificate of conformity with technical requirements in:)
API STANDARD 6FA FOURTH EDITION, JUNE 2018

Certificate No.:267103

Ref. Test report No.:267104

Name and postal address of manufacturer: DBV Valve Co., Ltd.

Tangtou Village, Oubei Street, Yongjia County,

PC: 325102, Wenzhou City, Zhejiang Province, P. R. China

(No.96 Fanhua East)

We hereby certify that the fire test on below valves have been conducted at the laboratory designated by manufacturer and witnessed by TÜV inspector according to requirements of API STANDARD 6FA FOURTH EDITION, JUNE 2018, the testing results of valves meet the requirements of API STAND ARD 6FA FOURTH EDITION, JUNE 2018

1. Description of Test Valve :

Q47F-CL1500 NPS2 Ball Valve
Ball Valve
2"
Class 1500
ASTM A105

2. Qualified Range of Valves:

Type	Ball Valves
Description of Valves	Ball Valves
Qualified Sizes (NPS) (according to API 6FA Table 4)	2",2 1/2",3",4"
Qualified Pressure Ratings (Class) (according to API 6FA Table 6)	1500;2500
Qualified Marking (according to API 6FA Para.4.5)	Qualified valves shall be permanently marked 6FA

This certificate is issued according to API STANDARD 6FA FOURTH EDITION, JUNE 2018, based upon the result of testing report on above mentioned test valve. The additional valves qualification shall be limited on similar valves of same basic design as the test valve and same nonmetallic materi als as the test valve in the seat-to-closure member seal, seat-to-body seal, stem seal, and body joint and seal according to API STANDARD 6FA FOURTH EDITION, JUNE 2018, Para.5.

Shanghai, January 10, 2020 (Place, date)

TÜV SÜD Industrie Service GmbH

Westendstr.199 80686 München Germany



CERTIFICATE

(Certificate of conformity with technical requirements in:)
API STANDARD 6FA FOURTH EDITION, JUNE 2018

Certificate No.:267105

Ref. Test report No.:267106

Name and postal address of manufacturer: DBV Valve Co., Ltd.

Tangtou Village, Oubei Street, Yongjia County,

PC: 325102, Wenzhou City, Zhejiang Province, P. R. China

(No.96 Fanhua East)

We hereby certify that the fire test on below valves have been conducted at the laboratory designated by manufacturer and witnessed by TÜV inspector according to requirements of API STANDARD 6FA FOURTH EDITION, JUNE 2018, the testing results of valves meet the requirements of API STAND ARD 6FA FOURTH EDITION, JUNE 2018

1. Description of Test Valve:

Q347F-CL600 NPS4 Ball Valve
Ball Valve
4"
Class 600
ASTM A105

2. Qualified Range of Valves :

Туре	Ball Valves
Description of Valves	Ball Valves
Qualified Sizes (NPS) (according to API 6FA Table 4)	4",6",8"
Qualified Pressure Ratings (Class) (according to API 6FA Table 6)	600;900
Qualified Marking (according to API 6FA Para.4.5)	Qualified valves shall be permanently marked 6FA

This certificate is issued according to API STANDARD 6FA FOURTH EDITION, JUNE 2018, based upon the result of testing report on above mentioned test valve. The additional valves qualification shall be limited on similar valves of same basic design as the test valve and same nonmetallic materials as the test valve in the seat-to-closure member seal, seat-to-body seal, stem seal, and body joint and seal according to API STANDARD 6FA FOURTH EDITION, JUNE 2018, Para.5.

Shanghai, January 10, 2020 (Place, date) Guilin Chen
TÜV SÜD Industrie Service GmbH

Westendstr.199 80686 München Germany